# 3M<sup>™</sup> Peltor<sup>™</sup> Technical Datasheet

## 3M <sup>™</sup> Peltor Ground Mechanic Adapters

FL5006 GB, FL5006-01, FL5006-02 GB, FL5006-03 GB

#### **Product desription**

The PTT button is logically placed so that it is easy to access with either hand. The design makes it easy to use even with heavy gloves. The PTT button has a specific pressure point. The jack is at a 10 degree angle to the fixed cord and positioned so that the headset is easy to plug in and unplug in all situations.

#### **Key Features:**

- Designed to fit the shape of the hand
- Clamp can be twisted 360 degrees
- Oil resistant cable

#### **Applications**

Ground Mechanic work (push back)

#### **Standards and Approval:**

The Product has been shown to meet the requirements of the European Directive 2004/108/EC and is thus CE marked. The product has been verified in accordance with EN61000-6-2:2005.

#### Size:

PTT house: 80x60x40 mm

### Materials and data:

Box: TPE

Cable: Self extinguishing PUR sheeting

| Connector and cable |
|---------------------|
|---------------------|

PTT house connector: 4-pole, TP-120 equivalent

FL5006-03 GB is equipped with a switch for constant PTT function for special purposes.

#### Use and storage:

Storage temperature: -20°C to +55°C, humidity <85%

Usage temperature: -20°C to +55°C Maximum recommended shelf life: 5 years

#### **Use limitations:**

Never modify or alter this product.



| $\odot$ |             |
|---------|-------------|
|         | * 100000000 |

| Model        | Cable                         | Connector       |
|--------------|-------------------------------|-----------------|
| FL5006 GB    | 6-cores neon green, 3,1-5,6 m | 3-pole ⊗ 6,3 mm |
| FL5006-01    | 6-cores black, 6,4-8,9 m      | 3-pole          |
| FL5006-02 GB | 6-cores neon green, 3,0-6,0 m | 3-pole          |
| FL5006-03 GB | 6-cores, neon green, 3,5-10 m | 3-pole          |



Comhead Headset Company GmbH Borsteler Chaussee 51 22453 Hamburg Germany

www.comhead.de (a) info@comhead.de \$\square\$ +49 40 500 580 20

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction. For complete warranty condition, contact your dealer or local 3M office.

## **Important Notice:**

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.